

Tile Testing

Sampling Requirements and Typical Turnaround

TEST METHOD	SAMPLING REQUIREMENTS	TYPICAL TURNAROUND
ASTM C370 Moisture		
Expansion	5 specimens, 1" x 4"	3 weeks
ASTM C372 Linear Thermal		
Expansion (Air)	1 whole specimen (Any size)	3 weeks
ASTM C372 Linear Thermal		
Expansion (Cryogenic)	1 whole specimen (Any size)	3 weeks
ASTM C373 Water Absorption	5 whole specimens	3 weeks
ASTM C424 Crazing		
Resistance	10 whole specimens	3 weeks
ASTM C482 Bond Strength	5 specimens, 4" x 4" with 1 original edge	3 weeks
ASTM C482 (Modified) Bond Strength	5 whole specimens The client must provide the thin-set, specify cure time needed and provide installation instructions for the set-up.	Depends on curing time specified
ASTM C484 Thermal Shock		
Resistance	5 whole specimens	3 weeks
ASTM C485, C499, C502		
Warpage, Dimensions &		
Wedging	10 whole specimens	3 weeks
ASTM C501 Taber Abraser	10 whole specimens	3 weeks
ASTM C609 Light Reflectance		
and Color Difference	5 specimens, 4" x 4"	3 weeks
ASTM C627 Robinson Floor Test	16 sq. ft. of material The client must provide all materials, except substrate. Please contact the lab for the additional form required.	6 weeks
ASTM C648 Breaking Strength	10 whole specimens	3 weeks
ASTM C650 Chemical Resistance	15 specimens, 2" x 2"	3 weeks
ASTM C1505 Modulus of		
Rupture	10 whole specimens	3 weeks
ASTM C895 Lead & Cadmium		
Extraction	6 specimens, 6" x 6" or larger	5 weeks
ASTM C1026 Freeze/Thaw	5 specimens, 3" x 3" Specimens to be cut from the center	4 months
	of 5 separate pieces.	
ASTM C1027 Surface		
Abrasion	16 specimens, 4" x 4"	3 weeks
ASTM C1028 Static		
Coefficient of Friction	3 specimens, 6" x 6" or larger	3 weeks
ASTM C1243 Deep Abrasion	5 specimens, 4" x 4"	3 weeks
ASTM C1378 Stain Resistance	6 specimens, 4" x 4"	3 weeks

4.CT. 4.040.TO. L	T	1
ASTM C1870 Impact	C	2
Resistance	6 specimens, 6" x 6"	3 weeks
ASTM C1895 Scratch	2, 12, 12, 12, 12, 12, 12, 12, 12, 12, 1	
Hardness	3 specimens, 3" x 12"	3 weeks
ASTM G21 Resistance to		
Fungi	1 specimen, 2" x 2"	3 weeks
ANSI A326.3 Dynamic		
Coefficient of Friction (Wet		_
Only)	3 specimens, 8" x 8" or larger	3 weeks
ANSI A326.3 Dynamic		
Coefficient of Friction (Dry		
Only)	3 specimens, 8" x 8" or larger	3 weeks
ANSI A326.3 Dynamic		
Coefficient of Friction (Wet +		
Dry)	3 specimens, 8" x 8" or larger	3 weeks
ASTM E303 Pendulum	3 whole specimens	3 weeks
	6 sq. ft. of material If grout is to be used, the client must	
DIN 16165 German Ramp	provide the grout, along with the grout joint size. If not,	3 weeks
Din 10103 German Kamp	grout is required, the specific installation layout for material	2 WEEKS
	must be submitted prior to testing.	
ISO 10545-2 Warpage,		
Dimensions, & Wedging	10 whole specimens	3 weeks
ISO 10545-3 Water		
Absorption	5 whole specimens	3 weeks
ISO 10545-4 MOR & Breaking		
Strength	10 whole specimens	3 weeks
ISO 10545-5 Coefficient of		
Restitution	5 specimens, 3" x 3"	3 weeks
ISO 10545-6 Deep Abrasion	5 specimens, 4" x 4"	3 weeks
ISO 10545-7 Surface Abrasion	16 specimens, 4" x 4"	3 weeks
ISO 10545-8 Linear Thermal		
Expansion	1 whole specimen (Any size)	3 weeks
ISO 10545-9 Thermal Shock		
Resistance	5 whole specimens	3 weeks
ISO 10545-10 Moisture	·	
Expansion	5 whole specimens	3 weeks
ISO 10545-11 Crazing	·	
Resistance	5 whole specimens	3 weeks
ISO 10545-13 Chemical	·	
Resistance	15 specimens, 2" x 2"	3 weeks
ISO 10545-14 Stain		
Resistance	6 specimens, 4" x 4"	3 weeks
<u> </u>		